

Baseboard Heater

Slim contoured design is the perfect complement for both contemporary and traditional decors.

Features

- Exclusive contoured design with full rounded end caps for safety and contemporary styling
- May be used with wall or unique side mounted built-in thermostat (not included)
- Large rear entry junction boxes on both sides of unit for quick and easy installation
- Full length automatic reset overheat protection for safety

Applications

- All residential applications, commercial offices, washrooms, meeting rooms, lobbies



Unique side mount optional thermostat may be installed from the rear without need to remove front panel.

Specifications

Voltage	120, 208, 240, 277 volts.
Wattage	Ten sizes ranging from 300W to 2500W.
Color	White or Almond
Finish	Specially-formulated epoxy/polyester powder coating is environmentally friendly and resists fading and abrasion.
Heating element	A nickel chromium element is totally enclosed within a stainless steel sheath providing superior life expectancy and resistance to rust. Aluminum fins are firmly staked to the surface to provide excellent heat transfer.
Installation	Large rear entry left and right junction boxes provide ease of installation.
Warranty	Ten year element warranty. One year warranty on complete unit. UL approved and CSA certified.



Control Options (field installed)

Thermostat kits

Cat. No.	Description	Rating
DTK-SP	Single pole built-in thermostat kit (adjustable)	120-240V, 17A 347V, 14A, 600V 10A
DTK-DP	Double pole built-in thermostat kit (adjustable)	120-240V, 17A 347V, 11A, 600V 10A
DTKT-SP	Single pole built-in tamperproof thermostat kit	120-240V, 17A 347V, 11A
DTKT-DP	Double pole built-in tamperproof thermostat kit	120-240V, 25A 347V, 11A 600V, 10A

Note: Each adjustable kit contains white and almond control knobs and hardware

Inside Corners

BNIC	Almond
BNICW	White

Note: Inside corners are used when continuous installation of baseboard cabinetry inside 90 degree corners is designed.

Relays

Cat. No.	Description	Rating
BLLVC11	Low voltage relay & transformer kit	120V, 22A
BLLVC21	Low voltage relay & transformer kit	208V, 22A
BLLVC31	Low voltage relay & transformer kit	240V, 22A
BLLVC41	Low voltage relay & transformer kit	277V, 17A
BLLVDU	Low voltage relay less transformer	120, 22A/208, 22A/ 240, 22A/277, 19A
BLLVD	Low voltage relay less transformer	120/208/ 240/277, 22A

Disconnect Switch Kits

BUS2	Double Pole
------	-------------

Ordering Guide

Cat. No.	Watts	BTU	Volts	Lgth. in.	Weight lbs.
(white)					
BN2203W11	300	1024	120	22 1/8	5.0
BN2203W21	300	1024	208	22 1/8	5.0
BN2203W31	300/225	1024/768	240/208	22 1/8	5.0
BN2805W11	500	1706	120	27 5/8	6.0
BN2805W21	500	1706	208	27 5/8	6.0
BN2805W31	500/375	1706/1280	240/208	27 5/8	6.0
BN2805W41	500/375	1706/1478	277/240	27 5/8	6.0
BN3907W11	750	2559	120	38 5/8	9.0
BN3907W21	750	2559	208	38 5/8	9.0
BN3907W31	750/563	2559/1919	240/208	38 5/8	9.0
BN3907W41	750/563	2559/1919	277/240	38 5/8	9.0
BN4810W11	1000	3412	120	47 5/8	10.0
BN4810W21	1000	3412	208	47 5/8	10.0
BN4810W31	1000/750	3412/2559	240/208	47 5/8	10.0
BN4810W41	1000/750	3412/2559	277/240	47 5/8	10.0
BN5712W11	1250	4265	120	56 11/16	12.0
BN5712W21	1250	4265	208	56 11/16	12.0
BN5712W31	1250/938	4265/3199	240/208	56 11/16	12.0
BN5712W41	1250/938	4265/3199	277/240	56 11/16	12.0

Cat. No.	Watts	BTU	Volts	Lgth. in.	Weight lbs.
(white)					
BN6615W11	1500	5118	120	65 3/4	13.0
BN6615W21	1500	5118	208	65 3/4	13.0
BN6615W31	1500/1125	5118/3839	240/208	65 3/4	13.0
BN6615W41	1500/1125	5118/3839	277/240	65 3/4	13.0
BN7517W21	1750	5971	208	74 3/4	16.0
BN7517W31	1750/1313	5971/4478	240/208	74 3/4	16.0
BN7517W41	1750/1313	5971/4478	277/240	74 3/4	16.0
BN8420W21	2000	6824	208	83 7/8	17.0
BN8420W31	2000/1500	6824/5120	240/208	83 7/8	17.0
BN8420W41	2000/1500	6824/5120	277/240	83 7/8	17.0
BN9322W21	2250	7677	208	92 7/8	19.0
BN9322W31	2250/1688	7677/5758	240/208	92 7/8	19.0
BN9322W41	2250/1688	7677/5758	277/240	92 7/8	19.0
BN10225W21	2500	8530	208	102	20.0
BN10225W31	2500/1875	8530/6398	240/208	102	20.0
BN10225W41	2500/1875	8530/6398	277/240	102	20.0

Note: 1) Standard color is White.
 2) To order Almond omit "W" in Cat. No.

Dimensions

