

Floor Drop-In Heater

Designed for fan-forced comfort where floor mounting is desired.



Features

- Compact design
- Superior finned tubular element design
- Manual and automatic reset thermal cutout provides protection against overheating
- Safety screen keeps foreign objects out
- Quick release interior for easier cleaning

Applications

- Hallways, entryways, solariums, & staircase landings

Ordering Guide

Cat. No.	Watts	BTU	Volts	Weight lbs.
FFIH15A31	375	1280	120	16
	750	2559	120	
	1125	3839	120	
	1500	5118	120	
	1500/1125	5118/3839	240/208	
	750/563	2559/1918	240/208	

Note: Standard color is almond. Add "W" at the end of Cat. No. for white.
Factory wired at 1500/1125W - 240/208V

Specifications

- Voltage** 120, 240/208 volts
- Wattage** Four outputs ranging from 375 to 1500W
- Color** Almond or White
- Airflow** 80 CFM
- Finish** Specially formulated polyester powder coating process is applied to the front panel which resists fading and abrasion.

Construction The housing is constructed of 18 gauge satin coat steel complete with knockouts to accommodate field wiring. The louvered grill is constructed of 14 gauge steel with 9 gauge trim.

Heating Element A nickel chromium element is totally enclosed within a steel sheath and spiral steel fins are brazed to the element to provide excellent heat transfer.

Controls & Wiring An external thermostat control (not included) is required to operate this unit. The unit is factory wired for 240/208V @ 1500/1125W operation and can be field wired to 120V @ 375W, 750W, 1125W or 1500W; 208V @ 563W or 750W; 240V @ 1125W

Warranty One year warranty on complete unit. UL and CSA approved.



Accessories (field installed)

Cat. No.	Description
FFIHWG	FFIH Grill kit (White)
FFIHAG	FFIH Grill kit (Almond)

Dimensions

